

QUICKSPECS

Compaq Value Monitors

MODELS

V75 Color Monitor

Model 623

307710-001

V90 Color Monitor

Model 631

305609-001

FOR MORE INFORMATION



Compaq Customer Support
(800) 263-5868



Web Site
www.compaq.ca



PaqFax
(800) 345-1518

STANDARD FEATURES

| | V75 Monitor | V90 Monitor |
|--|---|---|
| Type | Color multiple scan with Invar Shadow Mask | Color multiple scan with Invar Shadow Mask |
| Picture Tube (diagonal) | 17 in Flat Square | 19 in Flat Square |
| Viewable (diagonal) | 16 in | 18 in |
| Pitch | 0.26 mm | 0.26 mm |
| Graphic Preset Modes¹ | | |
| 1600 x 1200 | — | 60 Hz and 75 Hz |
| 1280 x 1024 | 60 Hz | 60 Hz, 75 Hz and 85 Hz |
| 1024 x 768 | 60 Hz, 75 Hz and 85 Hz | 60 Hz, 75 Hz and 85 Hz |
| 800 x 600 | 60 Hz, 75 Hz and 85 Hz | 60 Hz, 75 Hz and 85 Hz |
| 640 x 480 | 60 Hz, 75 Hz | 60 Hz, 75 Hz and 85 Hz |
| 640 x 350 | — | 70 Hz and 85 Hz |
| Text Mode (720 x 400) | 70 Hz | 70 Hz and 85 Hz |
| Mac Compatible Modes² | | |
| 832 x 624 | 74.5 Hz | 74.5 Hz |
| 1152 x 864 | — | 75 Hz |
| User-Programmable Modes | Four | Fifteen |
| Anti-Glare/Anti-Static | Yes/Yes | Yes/Yes |
| Plug and Play | Yes | Yes |
| Agency Approvals/Certifications | | |
| UL Approval | Yes | Yes |
| ISQ924 1-3 VOT Guidelines Approval | Yes | Yes |
| MPR II Compliant | Yes | Yes |
| FCC Approval | Yes | Yes |
| Energy Star Compliant | Yes | Yes |
| Microsoft PC97 Certified | Yes | Yes |
| TCO 95 Compliant | Yes | Yes |
| Analog Controls | Yes | Yes |
| Brightness, Contrast | Yes | Yes |
| On Screen Controls | Yes | Yes |
| Language Selection | Yes | Yes |
| User Controls | | |
| Size and Positioning | Yes | Yes |
| Pincushion (barrel) | Yes | Yes |
| Trapezoid | Yes | Yes |
| Tilt (rotation) | Yes | Yes |
| Color Temperature | No | Yes |
| Parallelogram | Yes | Yes |
| Pin Balance | No | Yes |
| Individual Color Control | No | Yes |
| Moire Cancellation | Yes | Yes |
| Convergence | No | Yes |
| Overscan | No | Yes |
| Serial Number Display | Yes | Yes |
| Power Saver on/off | Yes | Yes |
| Display Mode | Yes | Yes |
| Degauss | Yes | Yes |
| Factory Reset | Yes | Yes |
| Intelligent Manageability | | |
| Asset Control | Yes | Yes |
| Fault Management | No | Yes |
| USB Capabilities | Yes | Yes |
| Pixel Clock Speed | 108 MHz | 202.5 MHz |
| Input Impedance | 75 ohms +/- 10% | 75 ohms +/- 3% |
| Horizontal Frequency | 30 - 69 kHz | 30 - 94 kHz |
| Vertical Frequency | 47.5 - 125 Hz | 48 - 160 Hz |
| Power Supply/ALS | Universal/Auto-Sensing | Universal/Auto-Sensing |
| Maximum Power Rating | < 115 watts | 135 watts |
| Synch Input | TTL separate synch | TTL separate synch |
| Signal Cable | 15-pin miniature D-sub | 15-pin miniature D-sub |
| Dimensions (h x w x d) | 17.1 x 16.5 x 17.1 in/43.5 x 42.1 x 43.6 cm | 19.9x19.05x18.74 in/ 48.4x48.4x47.5cm |
| Weight | 44.1 lb/22 kg | 51.5 lb/25.2 kg |
| Humidity (non-condensing) and Operating Temperature | 20-80%; /50 to 104 degrees F | 20-80%; /50 to 140 degrees F |
| Limited Warranty³ | Three year parts, first-year labour on-site | Three year parts, first-year labour on-site |

¹All modes are noninterlaced unless specified otherwise.

²Adapter required.

³Certain restrictions and exclusions apply. Contact the Compaq Customer Support Centre at (800) 263-5868 for further details.

©1998 Compaq Computer Corporation. All rights reserved. Compaq is a trademark of Compaq Computer Corporation. The information in this publication is subject to change without notice. Printed in Canada.

COMPAQ